

## motorcycle battery mf range

# ZPOWER

### Never Says No.....

- Longer life cycle
- High cranking power
- Vibration resistance performance & good charging acceptance
- Low self discharge
- Consistent Performance quality
- Dry charge
- AGM Technology
- Advance calcium lead alloy technology, MF design
- Application of COS & TTP









































### General Features

1. *High Capacity ,Long life*
2. *Sealing structure of PP materials*
3. *High CCA and good starting performance*
4. *Good charging acceptance and vibration resistant performance*
5. *Application of AGM technology*
6. *Application of COS and TTP*
7. *Advanced sulfate-resistant technology*
8. *Advanced calcium lead alloy technology, maintenance-free design*
9. *Dependable design of leakage resistant and valve regulated sealing*
10. *Dry charged design, long storage time and can be used at any time you*
11. *full ranges models, good appearance and high standard design*

### Typical Applications

1. *AVT*
2. *Jet ski*
3. *Motorcycle*
4. *Snowmobile*
5. *Lawn & Garden*

### Terminal picture

Terminal Type	Front	Side	Terminal Type	Front	Side	Terminal Type	Front	Side
A			B			C		
								
D			E			F		
								
G			I			J		
								
H								
								

### Specifications

Model	Voltage	Capacity	CCA	Battery Size mm(±2mm)			Terminal	Charging current
	(V)	at 10 AH	@°F (-18°C) A	L	W	H		A
6N4-BS	6	4	N/A	70	70	95	/	0.4

N2.5LC	12	2.5	25	80	70	105	/	0.3
N3L-BS	12	3	35	98	56	110	B	0.3
NR4A-BS	12	2.3	45	113	48	85	I	0.2
N4B-BS	12	2.3	40	113	38	85	J	0.2
NX4L-BS	12	3	50	113	70	85	A	0.3
N4AL-BS	12	4	60	120	70	92	A	0.4
NX5L-BS	12	4	70	113	70	105	A	0.4
N5AL-BS	12	5	75	120	60	130	B	0.5
NX7A-BS	12	6	90	150	87	93	A	0.6
N7B-BS	12	6.5	85	150	65	93	A	0.7
NX7L-BS	12	6	85	113	70	130	A	0.6
N7DL-BS	12	7	90	150	60	130	B	0.7
NX9-BS	12	8	120	150	87	105	A	0.8
N9LBZ	12	9	120	135	75	139	B	0.9
N9B-BS	12	8	115	150	69	105	A	0.8
NX10L-BS	12	10	160	135	90	145	A	1
N12B-BS	12	10	175	150	69	130	A	1
NX12-BS	12	10	180	150	87	130	A	1
NX12L-BS	12	10	180	150	87	130	A	1
NX14-BS	12	12	200	150	87	145	A	1.2
NX14L-BS	12	12	200	150	87	145	A	1.2
NX14AH-BS	12	12	210	135	90	164	A	1.2
NX14AHL-BS	12	12	210	135	90	164	A	1.2
N14B-BS	12	12	210	150	69	145	A	1.2
NX15-BS	12	13	230	175	87	130	A	1.3
NX15L-BS	12	13	230	175	87	130	A	1.3
NX16-BS	12	14	230	150	87	161	A	1.4
NX16L-BS	12	14	230	150	87	161	A	1.4
NX16-BS-1	12	14	230	150	87	161	E	1.4
N16CL-BS	12	19	260	175	100	175	A	1.9
NX18-BS	12	18	250	205	87	162	A	1.8
NX18L-BS	12	18	250	205	87	162	A	1.8
NX20-BS	12	18	270	175	87	155	A	1.8
NX20L-BS	12	18	270	175	87	155	A	1.8
NX20CH-BS	12	18	270	150	87	161	A	1.8
NX20H-BS	12	18	310	175	87	155	A	1.8
NX20HL-BS	12	18	310	175	87	155	A	1.8
NX20HL-BS-PW	12	18	310	175	87	175	A	1.8
NX24H-BS	12	21	350	205	87	162	A	2.1
NX24HL-BS	12	21	350	205	87	162	A	2.1