

commercial vehicle battery heavy duty range

ZPOWER

Never Says No...

- Longer Life cycle
- High cranking power
- Vibration resistance performance and good charging acceptance
- Low self discharge
- Consistant performance quality
- Dry charge



Heavy Duty / Commercial vehicles (Dry charge)

Heavy Duty / Commercial Vehicles (Dry Charge - JIS range)												
Battery Type		Voltage (V)	Capacity At 20 Hr Rate (AH)	Cranking Ampere At 0°F (Amps)	Max. Overall Dimension (mm)				Cell Lay Out (Fig No.)	Terminal Design	Approx Acid Volume (L)	Base Hold Down
Old Type JIS	New Type JIS				Length	Width	Height	T.Height				
N70	65D31R	12	70	470	306	173	204	225	1	A	5.5	-
N70L	65D31L	12	70	470	306	173	204	225	0	A	5.5	-
N70Z	75D31R	12	75	550	306	173	204	225	1	A	5	-
N70ZL	75D31L	12	75	550	306	173	204	225	0	A	5	-
N100A/AL	--	12	95	--	410	176	213	234	1/0	A	-	-
N100/L	95E41R/L	12	100	512	410	176	213	234	1/0	A	-	-
N100Z/ZL	105E41R/L	12	105	577	410	176	213	234	1/0	A	-	-
N120A	--	12	110	--	505	182	213	257	4	A	-	-
N120	115F51	12	120	638	505	182	213	257	4	A	-	-
N135 / N150A	--	12	135	--	508	222	213	257	4	A	-	-
N150	145G51	12	150	754	508	222	213	257	4	A	-	-
N165	165G51	12	165	933	508	222	213	257	4	A	-	-
N180 / N200A	--	12	180	--	521	278	220	270	4	A	-	-
N200	190H52	12	200	924	521	278	220	270	4	A	-	-